

# AC-J9

## 低损射频电缆

### Low Loss RF Test Cable



电气性能 / Electrical Specifications	
频率范围 / Frequency Range	DC~26.5GHz
阻抗 / Impedance	50Ω
传输速率 / Velocity of Propagation	83%
屏蔽效能 / Shielding Effectiveness	<-90dBc
典型插损 / Typical Insertion Loss	0.78dB/m @ 10GHz
	0.86dB/m @ 12GHz
	1.00dB/m @ 16GHz
	1.06dB/m @ 18GHz
	1.35dB/m @ 26.5GHz
机械性能 / Mechanical Specifications	
最小弯曲半径 / Minimum Bend Radius	50mm
标称重量 / Weight	50g/m
温度范围 / Temperature Range	-55~+165°C
规格尺寸 / Dimensions	
中心导体 / Center Conductor	1.42mm
编织层 / Inner Braid	4.35mm
外径 / Overall Diameter	4.80mm

1. 中心导体 / Center Conductor	Silver Plated Copper	
2. 介质 / Dielectric	LD PTFE	
3. 屏蔽层 / Electrical Shield	Silber Plated Copper foil	
4. 编织层 / Inner Braid	Silver Plated Copper	
5. 护套 / Jacket	FEP	